



***GOLDENSTONE***



**PRODUCT CATALOGUE**

# HHT - 65

## Features:

- ❖ Unique high way rib pattern for excellent steering response and outstanding traction
- ❖ Suitable for highway application
- ❖ Strong nylon casing for better impact resistance
- ❖ Excellent mileage tread compound



| Tyre Size | PR | Type    | NSD (un-inflated) mm | Over all Diameter (mm) | Section Width (mm) | Max Load / Tyre (Kg) |      | Rec. Rim size |
|-----------|----|---------|----------------------|------------------------|--------------------|----------------------|------|---------------|
|           |    |         |                      |                        |                    | Single               | Dual |               |
| 7.00-15   | 10 | Bias TT | 10.0                 | 749                    | 198                | 1080                 | 1030 | 5.5F          |
| 7.00-15   | 12 | Bias TT | 10.0                 | 749                    | 198                | 1170                 | 1040 | 5.5F          |
| 7.50-15   | 12 | Bias TT | 10.2                 | 770                    | 217                | 1370                 | 1210 | 6.00G         |
| 7.00-16   | 10 | Bias TT | 11.2                 | 779                    | 198                | 1130                 | 1075 | 5.50F         |
| 7.00-16   | 12 | Bias TT | 11.2                 | 779                    | 198                | 1230                 | 1170 | 5.50F         |
| 7.50-16   | 12 | Bias TT | 10.4                 | 800                    | 219                | 1440                 | 1370 | 6.00G         |

# ATY - 55

## Features:

- ❖ Unique lug pattern for better road grip
- ❖ Suitable for highway application
- ❖ Strong nylon casing for better over load performance
- ❖ Heat resistant tread compound for cooler running



| Tyre Size | PR | Type    | NSD (un-inflated) mm | Over all Diameter (mm) | Section Width (mm) | Max Load / Tyre (Kg) |      | Rec. Rim size |
|-----------|----|---------|----------------------|------------------------|--------------------|----------------------|------|---------------|
|           |    |         |                      |                        |                    | Single               | Dual |               |
| 7.00-16   | 10 | Bias TT | -                    | -                      | -                  | 1130                 | 1105 | -             |
| 7.00-16   | 12 | Bias TT | 14.5                 | 787                    | 198                | 1230                 | 1170 | 5.50F         |
| 7.50-16   | 14 | Bias TT | -                    | -                      | -                  | 1510                 | 1440 | -             |